

Eco-Friendly & Professional

LED WIDESCREEN ULTRA HD DISPLAY 84WS70

**84" EDGE LED LARGE SCREEN**

Providing immersive wide viewing with high quality.

**SUPER HIGH RESOLUTION
3,840 x 2,160 (ULTRA HD)**

By realizing the LED display with the large screen size, super high resolution becomes possible to offer high realistic sensation and immersiveness.



84WS70

**HYBRID TYPE MEDIA PLAYER
BUILT-IN READY**

Making your signage look even slimmer and helps you maintain the system far more conveniently.



MP700, MP500

Hybrid Type Media Player

LED WIDESCREEN ULTRA HD DISPLAY

84WS70 84U"



FEATURES

- 84" Edge LED Large Screen
- Super High Resolution : 3,840 x 2,160 (Ultra HD)
- Clear & Vivid Picture (Dynamic CR : 500,000 : 1)
- Auto Brightness Sensor
- Smart Energy Saving
- Hybrid Type Media Player Built-in Ready (MP700, MP500)

SPECIFICATIONS

84WS70

PANEL	Screen Size	84U"
	Panel Technology	IPS
	Aspect Ratio	16 : 9
	Native Resolution	3,840 x 2,160 (Ultra HD)
	Brightness	500nit
	Contrast Ratio	1,400 : 1
	Dynamic CR	500,000 : 1
	Viewing Angle (H x V)	178 x 178
	Response Time	12ms (G to G) typ.
	CONNECTIVITY	Input
Digital		HDMI(2), DVI-D(1), Display Port(1) with HDCP for all input
Analog		Composite(1), RGB(1)
Audio		RGB, DVI-D, AV
External Control		RS232C(1), RJ45(1), IR(1, Internal)
USB		USB 2.0(2)
Output		
Digital		DVI-D(1)
Analog		RGB(1)
Audio		Yes(1), Line out(1)
External Control		RS232C(1), IR(1, Internal)
Audio		
Auto Volume		No
Balance		Yes
Audio Power	20W (10W x 2)	
Speaker On/off	Yes	
Clear Voice II	Yes	
Sound mode	Standard, Music, Cinema, Sports, Game, Vivid, User Setting	

PHYSICAL SPECIFICATION	Bezel Width	27.9mm
	Monitor Dimension (W x H x D)	192.3cm x 110.9cm x 5.1cm (Including Handle : 101cm)
	Weight (head)	72.9Kg
	Carton Dimensions (W x H x D)	203.4cm x 121.3cm x 31.4cm
	Packed Weight	87.2Kg
	VESA™ Standard Mount Interface	600mm x 400mm
SPECIAL FEATURES	Additional	Smart Energy Saving, Temp Sensor, Auto Brightness Sensor, ISM Method, Key Lock
ENVIRONMENT CONDITIONS	Operation Temperature	0°C ~ 40°C
	Operation Humidity	10% ~ 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Consumption	
	Typical / Smart Energy Saving	350W(Typ) / 200W(SES)
	DPMS	1.5W
	Power Off	0.5W
STANDARD(CERTIFICATION)	Safety	UL, cUL, CB scheme, TUV
	EMC	FCC Class 'A', VCCI, C-tick, CE, KCC
	ErP / Energy Star	Yes / No
MEDIA PLAYER COMPATIBILITY	Slot PC Compatible (optional)	Yes (MP700, MP500)
	External Media player Attachable	No
SOFTWARE COMPATIBILITY	Supersign Compatibility	Elite-w lite (Only Control), Elite-c
ACCESSORY	Included	D-Sub Cable, Power Cord, Remote Controller (include battery 2ea), CD (Manual/Elite-C/ESG), Eye Ball(2EA)
	Optional	MP700, MP500, SP-2000, LSW630

※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

DIMENSION (unit : mm)

